




F14.1 **Pumping Motion** Top Leaky Piston < **Outlet Pipe** Driving Cable_ Cylinder / Downpipe Piston Check Valve (ball valve) Bottom Leaky Piston Bottom Check Valve (ball valve) BEST AVAILABLE COPY















Huil Staff Marker Marker ridid sede -one way vdve Piston external Sleeve onl way • value. sealed -cylinler Same stiffor flexible drive rigid drive hole pipe or any pipe formed by connecting two whiles F14 5



F14.6

This Page is Inserted by IFW Indexing and Scanning Operations and is not part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

□ BLACK BORDERS
□ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
□ FADED TEXT OR DRAWING
□ BLURRED OR ILLEGIBLE TEXT OR DRAWING
□ SKEWED/SLANTED IMAGES
□ COLOR OR BLACK AND WHITE PHOTOGRAPHS
□ GRAY SCALE DOCUMENTS
□ LINES OR MARKS ON ORIGINAL DOCUMENT
□ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
□ OTHER:

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.